



HOSE TYPE:

1/4" VAMAC

- **TUBE:** VAMAC
- **VAMAC COMPOUND:** 7100 TO RSE/STD/004 PART 10
- **REINFORCEMENT:** ONE TEXTILE BRAID (POLYESTER)
- **OVER:** VAMAC
- **HOSE ID:** 6.3mm (+/- 0.5)
- **HOSE OD:** 16.4mm (+/- 0.5)
- **WORKING PRESSURE:** 20 BAR
- **MINIMUM BURST PRESSURE:** 80 BAR
- **TEMPERATURE RANGE:** -38°C TO +150°C
(CONTINUING OPERATING TEMPERATURES IN EXCESS OF THE SPECIFIED RANGE WILL SHORTEN THE LIFE OF THE HOSE)
- **MINIMUM BEND RADIUS:** 38mm
- **APPROXIMATE WEIGHT:** 0.39kg/m
- **CONFORMS TO:** Westinghouse Specification 9L67/68
- **MEETS FIRE SAFETY REGS:** BS 6853 CAT 1A
- **COMMENTS:** LOW SMOKE, LOW TOXICITY
- **TYPICAL USE:** UNDERGROUND BRAKE HOSE

BRANDING TYPICALLY:

1/4" - www.vamac.co.uk - TRJL  RSE/STD/004/PT10  BC: CO 14055 

We are the main supplier of Vamac Hose Assemblies in the UK
Email: sales@vamac.co.uk Tel: 01773 863000