



HOSE TYPE:

3/4" VAMAC

- TUBE: VAMAC
- VAMAC COMPOUND: 7100 TO RSE/STD/004 PART 10
- REINFORCEMENT: ONE TEXTILE BRAID (POLYESTER)
- OVER: VAMAC
- HOSE ID: 19mm (+/- 0.5)
- HOSE OD: 29.5mm (+/- 0.5)
- WORKING PRESSURE: 20 BAR
- MINIMUM BURST PRESSURE: 80 BAR
- TEMPERATURE RANGE: -38°C TO +150°C
(CONTINUING OPERATING TEMPERATURES IN EXCESS OF THE SPECIFIED RANGE WILL SHORTEN THE LIFE OF THE HOSE)
- MINIMUM BEND RADIUS: 114mm
- APPROXIMATE WEIGHT: 0.68kg/m
- CONFORMS TO: Westinghouse Specification 9L67/68
- MEETS FIRE SAFETY REGS: BS 6853 CAT 1A
- COMMENTS: LOW SMOKE, LOW TOXICITY
- TYPICAL USE: UNDERGROUND BRAKE HOSE

BRANDING TYPICALLY:

3/4" - www.vamac.co.uk - TRJL  RSE/STD/004/PT10  BC: CO 14055 

We are the main supplier of Vamac Hose Assemblies in the UK
Email: sales@vamac.co.uk Tel: 01773 863000